Network Working Group
INTERNET-DRAFT

S.E. Hardcastle-Kille
ISODE Consortium
November 1992
Expires: June 1993

Use of the Directory to support mapping between X.400 and RFC 822 Addresses

Status of this Memo

This document is an Internet Draft. Internet Drafts are working documents of the Internet Engineering Task Force (IETF), its Areas, and its Working Groups. Note that other groups may also distribute working documents as Internet Drafts.

Internet Drafts are draft documents valid for a maximum of six months. Internet Drafts may be updated, replaced, or obsoleted by other documents at any time. It is not appropriate to use Internet Drafts as reference material or to cite them other than as a "working draft" or "work in progress."

Please check the I-D abstract listing contained in each Internet Draft directory to learn the current status of this or any other Internet Draft.

Abstract

This document defines how to use directory to support the mapping between X.400 O/R Addresses and mailboxes defined in RFC 1327 [Kil92].

This draft document will be submitted to the RFC editor as a protocol standard. Distribution of this memo is unlimited. Please send comments to the author or to the discussion group <mhs-ds@mercury.udev.cdc.com>.

1 RFC 1327 Mappings

It is important to be able to represent RFC 1327 mappings in the directory [Kil92]. The three RFC 1327 mappings are represented within the O/R Address and Domain hierarchies within the DIT [HK91, HK92b].

The benefits of using the existing O/R address and domain trees are:

- It is the "natural" location, and will also help to ensure correct administrative authority for a mapping definition.
- The tree will usually be accessed for routing, and so it will be efficient for addresses which are being routed.
- This efficiency can be increased by representing mappings which can be derived from the basic mappings, as define in [HK92a].

> *An alternative approach which is not taken is to locate the information in separate subtrees, as defined in [HK92b]. By representing the information in separate subtrees, the mapping information would be kept in a clearly defined area which can be widely replicated in an efficient manner. This is not done, as the benefits of the approach proposed are greater.*

The values of the table mapping are defined by use of two new object classes, as specified in Figure 1.

2 Mapping from X.400 to RFC 822

As an example, consider the mapping from the O/R Address:

```
PRMD=UK.AC; ADMD=Gold 400; C=GB
```

This would be keyed by the directory entry:

```
PRMD=UK.AC, ADMD=Gold 400, C=GB
```

and return the mapping from the `associatedDomain` attribute, which gives the domain which this O/R address maps to. This attribute is used to define authoritative mappings, which are placed in the open community tree. The manager of an RFC 1327 mapping should make the appropriate entry.

To improve efficiency, the same information is made available in other places. There are two cases:

1. Representation of mapping information in routing trees other than the open community tree.

```
rFC822ToX400Mapping OBJECT−CLASS
   SUBCLASS OF domain−component
   MAY CONTAIN {
         associatedORAddress,
         nonAuthoritativeAssociatedORAddress,
         associatedX400Gateway}
   ::= oc−rfc822−to−x400−mapping

x400ToRFC822Mapping OBJECT−CLASS
   SUBCLASS OF or−address−component                                    10
   MAY CONTAIN {
         associatedDomain,
         nonAuthoritativeassociatedDomain}
   ::= oc−x400−to−x400−mapping


associatedORAddress ATTRIBUTE
   SUBTYPE OF mhs−or−addresses
   SINGLE VALUE
   ::= at−associated−or−address                                        20

nonAuthoritativeAssociatedORAddress  ATTRIBUTE
   SUBTYPE OF associatedORAddress
   SINGLE VALUE
   ::= at−non−authoriatative−associated−or−address

associatedX400Gateway ATTRIBUTE
   SUBTYPE OF mhs−or−addresses
   SINGLE VALUE
   ::= at−associated−x400−gateway                                      30

nonAuthoritativeassociatedDomain ATTRIBUTE
   SUBTYPE OF associatedDomain
   SINGLE VALUE
   ::= at−non−authoritative−associated−domain
```

Figure 1: Object Classes for RFC 1327 mappings

2. Representing a hierarchically derived mapping. For example, a mapping could be stored in the entry:

   `MHS-O=Salford, PRMD=UK.AC, ADMD=Gold 400, C=GB`

   This information could be derived from information in the entry:

   `PRMD=UK.AC, ADMD=Gold 400, C=GB`

   However, it would take an extra lookup to find this information.

This information is stored by use of the `nonAuthoritativeAssociatedDomain` attributes. For example, the entry

`MHS-O=UCL, PRMD=UK.AC, ADMD=Gold 400, C=GB`

could have a `nonAuthoritativeAssociatedDomain` attribute of value "`UCL.AC.UK`". It is the responsibility of the manager of the entry to track changes in authoritative mappings.

Functionally, mapping takes place exactly according to RFC 1327. The longest match is found by the following algorithm.

1. Take the O/R Address, and derive a directory name. This will be the O/R Address as far as the lowest OU.
2. Look up the entire name derived from the RFC 1327 key in a convenient routing tree. For authoritative information, the open tree must be used, but for performance reasons, another tree will usually be used [1].
3. Check for `associatedDomain` or `nonAuthoritativeAssociatedDomain` attributes.
   - If the mapped value is present, stop.
   - If not, strip one component of the name, and repeat.

If the non-authoritative information is provided, the mapping can always be achieved with two lookups.

[1] It may be sensible to define an attribute which indicates the tree that an MTA uses for this purpose.

3 Mapping from RFC 822 to X.400

There is an analogous structure for mappings in the reverse direction. The domain hierarchy is represented in the DIT according to RFC 1279. The domain:

```
AC.UK
```

Is represented in the DIT as:

```
DomainComponent=AC, DomainComponent=UK, O=Internet
```

This has associated with it the attribute `associatedORAddress`, with a value:

```
PRMD=UK.AC; ADMD=Gold 400; C=GB
```

There is an optimisation analogous to the reverse mapping provided by the `nonAuthoritativeORAddress` attribute.

The "table 3" mapping is provided by the `associatedX400Gateway` attribute. This value may be different in different routing trees, as this is not a globally unique mapping. It is also possible to identify multiple possible associated gateways. This information is looked up at the same time as mapped O/R addresses. In effect, this provides a fallback mapping, which is found if there is no equivalence mapping. Functionally, mapping takes place exactly according to RFC 1327. The longest match is found by the following algorithm.

1. Derived a directory name from the domain part of the RFC 822 address.
2. Look up this name to find the mapped value (`associatedORAddress` or `nonAuthoritativeAssociatedORAddress` o `associatedX400Gateway`.).
   - If the mapped value is present, stop.
   - If not, strip one component of the name, and repeat.

If multiple `associatedX400Gateway` attributes are found, the MTA may select the one it chooses to use. If the non-authoritative information is provided, the mapping can always be achieved with two lookups.

Because of the availability of aliases, some of the table mappings may be simplified. In addition, the directory can support mapping from addresses using the numeric country codes.

References

[HK91] S.E. Hardcastle-Kille. X.500 and domains. Request for Comments RFC 1279, Department of Computer Science, University College London, November 1991.

[HK92a] S.E. Hardcastle-Kille. MHS use of the directory to support MHS routing, April 1992. Internet Draft.

[HK92b] S.E. Hardcastle-Kille. Representing the O/R Address hierarchy in the directory information tree, April 1992. Internet Draft.

[Kil92] S.E. Kille. Mapping between X.400(1988) / ISO 10021 and RFC 822. Request for Comments 1327, Department of Computer Science, University College London, May 1992.

4 Security Considerations

Security considerations are not discussed in this INTERNET–DRAFT .

5 Author's Address

Steve Hardcastle-Kille
ISODE Consortium
PO Box 505
London
SW11 1DX
England

Phone: +44-71-223-4062

EMail: S.Kille@ISODE.COM

DN: CN=Steve Hardcastle-Kille,
O=ISODE Consortium, C=GB

UFN: S. Hardcastle-Kille, ISODE Consortium, GB

A Object Identifier Assignment

mhs−ds **OBJECT−IDENTIFIER** ::= {iso(1) org(3) dod(6) internet(1) private(4)
enterprises(1) isode−consortium (453) mhs−ds (3)}

mapping **OBJECT IDENTIFIER** ::= {mhs−ds 4}

oc **OBJECT IDENTIFIER** ::= {mapping 1}
at **OBJECT IDENTIFIER** ::= {mapping 2}

oc−rfc822−to−x400−mapping **OBJECT IDENTIFIER** ::= {oc 1}
oc−x400−to−x400−mapping **OBJECT IDENTIFIER** ::= {oc 2}

at−associated−or−address **OBJECT IDENTIFIER** ::= {at 1}
at−non−authoriatative−associated−or−address **OBJECT IDENTIFIER** ::= {at 2}

at−associated−domain **OBJECT IDENTIFIER** ::= {at 4}
at−non−authoritative−associated−domain **OBJECT IDENTIFIER** ::= {at 5}

Figure 2: Object Identifier Assignment